2015 EXPEDITION® LE

PACKAGE HIGHLIGHTS

- REV-XU™ platform
- SC™-5U articulating rear suspension
- Locking mechanism on one side (no tool required) for articulated suspension
- 500 x 3923 x 38 mm track
- Adjustable ski stance
- **Pilot® DS 2 skis**
- 580 mm one piece windshield with mirrors
- Multifunction digital gauge with engine temperature
- Electric start
- Synchromesh transmission with reverse (2-1-N-R)
- Heated driver's visor power outlet
- Rack and hitch
- 12 V power outlet
- Modular 2-up seat with underseat storage
- Air radiator with fan
- Adjustable, heated passenger handgrips

EXTRA HIGHLIGHTS

900 ACE™

- **Rotax® 900 ACE engine with 650 W magneto**
- **Reversible throttle lever (thumb or finger activated)**
- Engine oil cooler
- **Engine mapping modes (Standard, Sport or ECO™)**
- **Learning Key included**

NEW features for 2015

ENGINE CHOICE

	Rotax 600 H.O. E-TEC®	Rotax 900 ACE
Engine details	Liquid-cooled, 3-D R.A.V.E.™	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	2	3
Displacement	594,4cc	899cc
Bore	72 mm	74 mm
Stroke	73 mm	69,7 mm
Maximum engine speed	8100 RPM	7250 RPM
Carburation	Electronic Direct Injection	EFI, 46 mm throttle body
Recommended fuel type	Premium unleaded	Regular unleaded
Minimum octane	95	95
Fuel tank	45 liters	45 liters
Oil tank capacity	2,8 liters	3,3 liters

POWERTRAIN

Drive clutch type	TRA™ III	eDrive™ 2
Driven clutch type	QRS	QRS (short shaft)
Engagement	3000 RPM	2200 RPM
Small sprocket number of teeth	1st gear = 3,23:1 ratio	1st gear = 3,23:1 ratio
Large sprocket number of teeth	2nd gear = 1,98:1 ratio	2nd gear = 1,98:1 ratio
Drive sprocket number of teeth	8	8
Drive sprocket diameter	183 mm	183 mm
Brake system	Hydraulic with braided stainless-steel brake line	Hydraulic with braided stainless-steel brake line

DRY WEIGHT

	278 kg	290 kg

COLOR CHOICE

Black

DIMENSIONS

Vehicle overall length	3230 mm
Vehicle overall width	1150 or 1192 mm
Vehicle overall height	1330 mm
Ski stance	975 or 1018 mm
Ski overall length	1040 mm
Track nominal width	500 mm
Track nominal length	3923 mm
Track profile height	38 mm

SUSPENSION

Front suspension	Dual A-arms
Front shock	HPG™
Front suspension max. travel	210 mm
Rear suspension	SC-5U
Center shock	HPG
Rear shock	HPG
Rear suspension max. travel	340 mm

FEATURES

Frame	REV-XU
Skis	Pilot DS 2
Seating	2-up modular with underseat storage
Backrest	Standard (adjustable)
Handlebar	Painted steel with J-hooks / Grab handle

Riser block height	205 mm
Electric start	Standard
Reverse	Mechanical
Heated throttle lever	Standard
Heated grips	Standard
Gauge	Multifunction
Mirrors	Standard

Windshield	580 mm
Carbide runner	Standard
Carbide configuration	102 mm square type at 90°
Hitch	J-hook type

©2014 Bombardier Recreational Products Inc., (BRP). All rights reserved. ™,® and the BRP logo are trademarks of BRP or its affiliates. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation.

ski-doo