

# 2015 GRAND TOURING™ SPORT



## PACKAGE HIGHLIGHTS

- Rotax® engine with 650 W magneto
- **REV-XS® platform**
- SC™-5M rear suspension
- **Straight aluminum handlebar with integrated J-hooks**
- **Lightweight 281 x 3487 x 32 mm lug RipSaw® track**
- Dual A-arms front suspension
- Pilot® DS 2 skis
- Brembo brake with braided stainless-steel brake line
- Excellent wind protection with an 450 mm windshield
- **Steering controls module**
- Electric start
- Mechanical reverse
- Heated passenger grips with air deflectors
- **Learning Key included**
- **Reversible throttle lever (thumb or finger activated)**
- Heated driver's visor power outlet
- Air radiator with fan & engine oil cooler
- Extended heat exchanger for better cooling capacity

NEW features for 2015

## ENGINE CHOICE

Engine	Rotax 600 ACE™
Engine details	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	2
Displacement	600cc
Bore	74 mm
Stroke	69,7 mm
Maximum engine speed	7250 RPM
Carburation	EFI
Recommended fuel type	Regular unleaded
Minimum octane	95
Fuel tank	40 liters
Oil tank capacity	2,1 liters

## COLOR CHOICE

White / White

## DIMENSIONS

Vehicle overall length	3110 mm
Vehicle overall width	1217 mm
Vehicle overall height	1275 mm
Ski stance	1077 mm
Ski overall length	1066 mm
Track nominal width	406 mm
Track nominal length	3487 mm
Track profile height	<b>32 mm RipSaw</b>

## SUSPENSION

Front suspension	Dual A-arms
Front shock	Motion Control
Front suspension max. travel	229 mm
Rear suspension	SC-5M
Center shock	Motion Control
Rear shock	HPG™
Rear suspension max. travel	340 mm

## POWERTRAIN

Drive clutch type	eDrive™ 2
Driven clutch type	QRS (short shaft)
Engagement	2200 RPM
Small sprocket number of teeth	21
Large sprocket number of teeth	49
Drive sprocket number of teeth	8
Drive sprocket diameter	183 mm
Brake system	Brembo brake with braided stainless-steel brake line

## DRY WEIGHT

231 kg

## FEATURES

Frame	<b>REV-XS</b>	Electric start	Standard	Windshield	450 mm
Skis	Pilot DS 2	Reverse	Mechanical	Carbide runner	Standard
Seating	2-up	Heated throttle lever	Standard	Carbide configuration	132 mm square type at 60°
Backrest	Standard (not adjustable)	Heated grips	Standard	Hitch	EU-type
Handlebar	<b>Aluminum with J-hooks</b>	Gauge	Analog with display		
Riser block height	115 mm	Mirrors	Standard		