

2015 TUNDRA™ XTREME



PACKAGE HIGHLIGHTS

- REV-XM™ running boards (large opening)
- REV-XU™ platform
- SC™-5U articulating rear suspension
- Locking mechanism on one side (no tool required) for articulated suspension
- Non-ported 406 x 3923 x 57 mm PowderMax⁺ track
- Lynx telescopic front suspension
- Pilot® DS 2 skis
- Brembo brake with braided stainless-steel brake line
- Forward steering position
- RF D.E.S.S. key
- Electric start
- RER™ electronic reverse
- HPG™ rear and center shocks
- Painted tunnel and bumpers
- LinQ™ attach kit (4)
- REV-XP® X narrow seat with 5 L of storage
- Aluminum handlebar with J-hooks
- Steering controls module

NEW features for 2015

ENGINE CHOICE

Engine	Rotax® 600 H.O. E-TEC®
Engine details	Liquid-cooled, 3-D R.A.V.E.™
Cylinders	2
Displacement	594,4cc
Bore	72 mm
Stroke	73 mm
Maximum engine speed	8100 RPM
Carburation	Electronic Direct Injection
Recommended fuel type	Premium unleaded
Minimum octane	95
Fuel tank	40 liters
Oil tank capacity	3,7 liters

COLOR CHOICE

Race Orange / Black 

DIMENSIONS

Vehicle overall length	3329 mm
Vehicle overall width	1002 mm
Vehicle overall height	1296 mm
Ski stance	813 mm
Ski overall length	1040 mm
Track nominal width	406 mm
Track nominal length	3923 mm
Track profile height	57 mm PowderMax

POWERTRAIN

Drive clutch type	TRA™ III
Driven clutch type	QRS
Engagement	3400 RPM
Small sprocket number of teeth	21
Large sprocket number of teeth	49
Drive sprocket number of teeth	8
Drive sprocket diameter	183 mm
Brake system	Brembo brake with braided stainless-steel brake line

SUSPENSION

Front suspension	LTS
Front shock	Motion Control
Front suspension max. travel	150 mm
Rear suspension	SC-5U
Center shock	HPG
Rear shock	HPG
Rear suspension max. travel	356 mm

DRY WEIGHT

225 kg

FEATURES

Frame	REV-XU	Riser block height	205 mm	Mirrors	Optional
Skis	Pilot DS 2	Electric start	Standard	Windshield	254 mm
Seating	REV-XP X narrow with storage	Reverse	RER	Carbide runner	Standard
Handlebar	Aluminum with J-hooks / Grab handle	Heated throttle lever	Standard	Carbide configuration	102 mm square type at 90°
		Heated grips	Standard	Hitch	Optional
		Gauge	Analog with display		

